


Certification



Specialty

- Constant Voltage
- Full-isolated, delivering up to 100W of power. Short circuit, over current and over voltage protection. Up to 80% efficient.
- Fireproof environmental protection case
- 3 years quality warranty


Details



Product Picture



Size



Technical Parameter

Input Voltage Range	90-130V&180-240V/AC		
AC Frequency	48-62Hz		
Input current	1.5Amax		
Output Mode	Constant Voltage		
Output Current	7000mA	4200mA	2100mA
On Load Voltage	12V	24V	48V
On Load Range	60%70%-100%		
Output Power	100W Max.		
Power Factor	>0.95		
Efficiency	>80%		
Dimensions	210*68*38(mm)		
Weight	503g		

Environmental Specifications

Operating Temperature	-30~45°C
Storage Temperature	-40~+70°C
Thermal Dissipation	Nature
Relative Humidity	5~95%
Isolation Voltage	In/Out 3000VAC
Vibration	5-55Hz/2g,30 Minutes
Life Time	50000Hours,at TC max

Conformity & Standards

EMI	EN55022 EN55015 Class B
Safety	EN60598
Electromagnetic Immunity	EN61547,ENV5024 EN61000-4-2/3/4/6/8/11
Harmonic Current Emissions	EN61000-3-2 EN61000-3-3